



Selby Series



FEATURES

- Die-Cast Aluminium Housing
- PMMA Lens
- LED Type: Citizen/Luminous COB
- Driver: Archi Flicker-Free
- Working Temperature Range: -15°C to 40°C
- Voltage: AC220-240V
- Power Factor: >0.90

OPTIONS

- 0-10V, Triac or DALI Dimmable
- Available in optional CCT: 2700/3000/3500/4000/5000/5700K
- Colour Render Index (CRI): >RA83/92
- Beam angles of 15°, 24°, or 36° available
- Available in black, white or custom colour trims

MODEL NO	WATTAGE	EFFICACY (Lumens/Watt)	SIZE	CUTOUT
AES-PS-DL8C24B-8W	8W	80	83mmØ x 95mmH	72mmØ
AES-PS-DL12C24B-12W	12W	80	83mmØ x 95mmH	72mmØ
AES-PS-DL15C24B-15W	15W	80	95mmØ x 116mmH	85mmØ
AES-PS-DL18C24B-18W	18W	80	95mmØ x 116mmH	85mmØ

Please add additional suffix to end of the above Catalogue Number if these options are to be included.

2700K	2.7K	3000K	3K	3500K	3.5K
4000K	4K	5000K	5K	5700K	5.7K
0-10V Dimmable	0-10V	Triac Dimmable	TRI	DALI Dimmable	DALI
White Trim	WT	Black Trim	BT	Custom Colour Trim	CT
Beam Angle 15°	15°	Beam Angle 24°	24°	Beam Angle 36°	36°
CRI >RA83	CRI83	CRI >RA92	CRI92		



AES
Australian EcoTech Solutions

A: 1/123 Merrindale Drive, Croydon South VIC 3136

P: (03) 8761 6734

E: sales@ausecotech.com.au

W: www.ausecotech.com.au



RoHS